## NSN 4720-01-056-1414

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-056-1414

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.828 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Red
Connection Style:
Plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Burst Test Pressure:
200.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
50.0 pounds per square inch
Thread Size:
0.500 inches 2nd end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
100.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
35.750 inches
Media For Which Designed:
Water single response
Thread Series Designator:

Npt 1st end

## NSN 4720-01-056-1414

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0