Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-056-9518

Cross Sectional Shape:	
Round	
Гhread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.851 inches	
Fempurature Rating:	
65.0 degrees fahrenheit and 450.0 deg	rees fahrenheit single response
Dutside Diameter:	
1.140 inches	
Minimum Inside Bending Radius:	
7.300 inches	
End Application:	
Grumman aircraft, model a10	
Connection Style:	
Swivel nut, flareless 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
3500.0 pounds per square inch	
ayer Composition And Location:	
st layer molded polytetrafluoroethylene	and 2nd layer braided corrosion resistant steel wire and outer layer braided corrosion resistant
steel wire	
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
1.312 inches 2nd end	
Hydrostatic Test Pressure:	
2500.0 pounds per square inch	
Flow Angle:	
0.0 degrees 2nd end	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
16.250 inches working	
Thread Series Designator:	
Jnjf 2nd end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A542a0