NSN 4720-01-057-3289

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-057-3289

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.183 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.325 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches working
Thread Series Designator:
Unf 2nd end

NSN 4720-01-057-3289

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0