Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-060-4552

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.375 inches	
Outside Diameter:	
1.500 inches	
Minimum Inside Bending Rad	us:
9.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
2000.0 pounds per square inch	
Layer Composition And Loca	ion:
Outer layer molded rubber, syn	
Maximum Operating Pressure	
500.0 pounds per square inch	
Thread Size:	
1.875 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
1000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Lengt	h:
360.000 inches working	
Media For Which Designed:	
Hydraulic fluid single response	
Thread Series Designator:	
Unj 1st end	
Shelf Life:	
N/a	

NSN 4720-01-060-4552

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0