

View Online at <https://aerobasegroup.com/nsn/4720-01-060-6074>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.230 inches

Temperature Rating:

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.380 inches

Minimum Inside Bending Radius:

1.500 inches

Exterior Color:

Natural

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nuts drilled for lockwire

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

10.000 millimeters 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.000 inches working

Thread Series Designator:

Iso m 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0