Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-060-6076

C	ross Sectional Shape:
	ound
	hread Direction:
	ight-hand 1st end
	side Diameter:
-	210 inches
	empurature Rating:
	7.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
	utside Diameter:
•	360 inches
	inimum Inside Bending Radius:
	500 inches
	xterior Color:
	atural
	onnection Style:
	wivel nut, flareless 1st end
	nd Connection Design:
	traight 1st end
	onnection Type:
	nreaded internal tube 1st end
Fe	eatures Provided:
	uts drilled for lockwire
B	urst Test Pressure:
12	2000.0 pounds per square inch
La	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
Μ	aximum Operating Pressure:
30	000.0 pounds per square inch
Tł	hread Size:
10	0.000 millimeters 1st end
Se	eat Angle:
12	2.0 degrees 1st end
Hy	ydrostatic Test Pressure:
60	000.0 pounds per square inch
In	side Surface Condition:
Sı	mooth
Μ	easuring Method And Length:
20	0.125 inches working
Tł	hread Series Designator:
ls	o m 1st end
S	helf Life:
N	/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0