NSN 4720-01-060-6078

Cross Sectional Shape:

Thread Direction: Right-hand 1st end

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-060-6078

Inside Diameter:					
0.210 inches					
Tempurature Rating:					
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response					
Outside Diameter:					
0.360 inches					
Minimum Inside Bending Radius:					
1.500 inches					
Exterior Color:					
Natural					
Connection Style:					
Swivel nut, flareless 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Nuts drilled for lockwire					
Burst Test Pressure:					
12000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
10.000 millimeters 1st end					
Seat Angle:					
12.0 degrees 1st end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
21.375 inches working					
Thread Series Designator:					
Iso m 1st end					
Shelf Life:					
N/a					

NSN 4720-01-060-6078

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0