NSN 4720-01-060-9146

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-060-9146	
Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.210 inches	
Tempurature Rating:	
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.360 inches	
Minimum Inside Bending Radius:	
1.500 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Nuts drilled for lockwire	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
10.000 millimeters 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.625 inches working

Special Features:

Second end connection is of special design

Thread Series Designator:

Iso m 1st end

NSN 4720-01-060-9146

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0