Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-060-9148

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.310 inches	
Tempurature Rating:	
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single	response
Outside Diameter:	
0.460 inches	
Minimum Inside Bending Radius:	
2.500 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Nuts drilled for lockwire	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
12.000 millimeters 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
14.125 inches working	
Thread Series Designator:	
Iso m 1st end	
Shelf Life:	
N/a	

NSN 4720-01-060-9148

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0