## NSN 4720-01-060-9149

**Cross Sectional Shape:** 

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.310 inches

**Tempurature Rating:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-060-9149

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.460 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
12.000 millimeters 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.625 inches working
Thread Series Designator:
Iso m 1st end
Shelf Life:
N/a

## NSN 4720-01-060-9149

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0