NSN 4720-01-060-9336

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-060-9336
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.210 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.360 inches
Minimum Inside Bending Radius:
1.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
10.000 millimeters 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Tost Proceure:

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

29.750 inches working

Special Features:

Second end connection is of special design

Thread Series Designator:

Iso m 1st end

NSN 4720-01-060-9336

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0