

View Online at <https://aerobasegroup.com/nsn/4720-01-061-0766>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.810 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

3.375 inches 2nd end

**Flange Thickness:**

0.438 inches 2nd end

**Outside Diameter:**

2.220 inches

**Minimum Inside Bending Radius:**

13.250 inches

**Bolt Hole Quantity:**

4 2nd end

**Flange Outside Diameter:**

5.000 inches 2nd end

**Connection Style:**

Plain 2nd end

**Bolt Hole Diameter:**

0.625 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Plain face flange 2nd end

**Burst Test Pressure:**

1400.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

350.0 pounds per square inch

**Hydrostatic Test Pressure:**

700.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

29.500 inches

**Flange Style:**

Round w/ bolt holes 2nd end

**Special Features:**

Furnished with one internal support coil of stainless steel

**Media For Which Designed:**

Hydraulic fluid single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0