

View Online at <https://aerobasegroup.com/nsn/4720-01-061-5933>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.310 inches

Temperature Rating:

-60.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.460 inches

Minimum Inside Bending Radius:

2.500 inches

Exterior Color:

Natural

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nuts drilled for lockwire

Burst Test Pressure:

10500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

16.000 millimeters 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.125 inches working

Special Features:

Second end is of special design

Thread Series Designator:

Iso m 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0