## NSN 4720-01-061-5933

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-061-5933
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.310 inches
Tempurature Rating:
-60.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.460 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
10500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
16.000 millimeters 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:

6000.0 pounds per square inch

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

15.125 inches working

**Special Features:** 

Second end is of special design

**Thread Series Designator:** 

Iso m 1st end

## NSN 4720-01-061-5933

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0