Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-062-3477

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.920 inches
Minimum Inside Bending Radius:
5.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
2400.0 pounds per square inch
Layer Composition And Location:
1st layer braided polyester cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
600.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1200.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
36.250 inches
Media For Which Designed:
Fuel/oil, hydrocarbon and water single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0