

View Online at <https://aerobasegroup.com/nsn/4720-01-063-3002>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

0.625 inches

Minimum Inside Bending Radius:

1.500 inches

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

225.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and ethylene glycol resistant and heat resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

27.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Air single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0