NSN 4720-01-063-3857

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-063-3857

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.219 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.625 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut, flareless 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 12.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 8000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant and fuel resistant and hydraulic solution resistant and oil resistant and weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 42.000 inches working |

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid single response

NSN 4720-01-063-3857

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator: |
|-----------------------------------|
| Unjf 1st end |
| Specification Data: |
| 96906-ms28762 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A542a0