

View Online at <https://aerobasegroup.com/nsn/4720-01-064-4184>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.766 inches

Minimum Inside Bending Radius:

4.625 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer rubber impregnated braided steel wire and outer layer molded rubber

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

38.000 inches excluding end fittings

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0