Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-064-5519

Cros	s Sectional Shape:
Rour	nd
Thre	ad Direction:
Right	t-hand 1st end
Insid	le Diameter:
0.250) inches
Tem	purature Rating:
-40.0	degrees fahrenheit and 200.0 degrees fahrenheit single response
Outs	ide Diameter:
0.590) inches
Mini	mum Inside Bending Radius:
4.000) inches
Exte	rior Color:
Black	κ
Con	nection Style:
Plain	1st end
End	Connection Design:
Strai	ght 2nd end
Conr	nection Type:
Threa	aded external pipe 2nd end
Feat	ures Provided:
Reus	sable end fittings
Burs	at Test Pressure:
2000	0.0 pounds per square inch
Laye	r Composition And Location:
1st la	ayer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maxi	mum Operating Pressure:
5000	0.0 pounds per square inch
Thre	ad Size:
0.250	0 inches 2nd end
Seat	Angle:
30.0	degrees 2nd end
Hydr	ostatic Test Pressure:
1000	0.0 pounds per square inch
Oute	r Covering Environmental Protection:
Abra	sion resistant and weatherproof
Insid	le Surface Condition:
Smo	oth
Meas	suring Method And Length:
48.50	00 inches
Medi	a For Which Designed:
	oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0