Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-064-6879

С	ross Sectional Shape:
	ound
	hread Class:
	o 1st end
-	hread Direction:
	ight-hand 1st end
	side Diameter:
	219 inches
-	empurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	utside Diameter:
	469 inches
-	inimum Inside Bending Radius:
	000 inches
-	onnection Style:
	wivel nut flare 2nd end
	nd Connection Design:
	traight 1st end
	onnection Type:
	hreaded internal tube 1st end
в	urst Test Pressure:
1!	5000.0 pounds per square inch
	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
M	aximum Operating Pressure:
3(000.0 pounds per square inch
T	hread Size:
0.	438 inches 1st end
S	eat Angle:
3	7.0 degrees 2nd end
Н	ydrostatic Test Pressure:
60	000.0 pounds per square inch
F	low Angle:
90	0.0 degrees 2nd end
In	side Surface Condition:
S	mooth
Μ	easuring Method And Length:
18	3.000 inches working
T	hread Series Designator:
U	njf 1st end
S	helf Life:
Ν	/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0