NSN 4720-01-064-8393

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-064-8393

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.313 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response				
Outside Diameter:				
0.672 inches				
Minimum Inside Bending Radius:				
4.000 inches				
Exterior Color:				
Black				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
9000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer molded rubber				
Maximum Operating Pressure:				
2000.0 pounds per square inch				
Thread Size:				
0.563 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
4500.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
46.000 inches excluding end fittings				
Media For Which Designed:				

media i oi willeli besignea.

Air and fuel/oil, hydrocarbon single response

NSN 4720-01-064-8393

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
1	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	D C3	igilatoi.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0