Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-065-4816

Cr	oss Sectional Shape:
	bund
	nread Class:
) 1st end
	nread Direction:
	ght-hand 1st end
	side Diameter:
	313 inches
Τe	empurature Rating:
	7.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	utside Diameter:
0.4	446 inches
Mi	inimum Inside Bending Radius:
	000 inches
Сс	onnection Style:
Sv	vivel nut with compression sleeve 2nd end
Er	nd Connection Design:
St	raight 1st end
Ca	onnection Type:
Th	nreaded internal tube 1st end
Th	nready Qty Per Inch (tpi):
18	3 1st end
Βι	urst Test Pressure:
90	00.0 pounds per square inch
La	ever Composition And Location:
Οι	uter layer braided corrosion resistant steel wire
Ma	aximum Operating Pressure:
15	00.0 pounds per square inch
Th	nread Size:
0.5	562 inches 2nd end
Se	eat Angle:
10	0.0 degrees 2nd end
Hy	/drostatic Test Pressure:
30	00.0 pounds per square inch
Fle	ow Angle:
90	0.0 degrees 2nd end
In	side Surface Condition:
Sr	nooth
Me	easuring Method And Length:
18	3.000 inches working
Th	nread Series Designator:
Ur	njf 1st end

NSN 4720-01-065-4816

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

