NSN 4720-01-066-4264

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-066-4264 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.125 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.531 inches **Minimum Inside Bending Radius:** 9.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 2500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 600.0 pounds per square inch **Thread Size:** 1.625 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 1250.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant **Inside Surface Condition:**

Smooth

Measuring Method And Length:

60.000 inches working

Thread Series Designator:

Unj 1st end

NSN 4720-01-066-4264

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0