

View Online at <https://aerobasegroup.com/nsn/4720-01-067-2572>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.230 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.380 inches

**Minimum Inside Bending Radius:**

1.500 inches

**Connection Style:**

Swivel nut, flareless 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

10.000 millimeters 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

18.875 inches working

**Thread Series Designator:**

Iso m 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0