NSN 4720-01-067-5938



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-067-5938 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.485 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 400.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and outer layer braided polyester cord **Maximum Operating Pressure:** 100.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 200.0 pounds per square inch **Inside Surface Condition:** Smooth

Hydrostatic Test Pressure:
200.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.000 inches working
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

NSN 4720-01-067-5938

Nonmetallic Hose Assembly - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A542a0