NSN 4720-01-067-9163

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-067-9163

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
0.970 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Mil-h-13531b, type ii, class a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in
specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on
certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Second End Relationship With First End:
Not identical
Burst Test Pressure:
14000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided steel wire err-100
Maximum Operating Pressure:

0.750 inches 2nd end

Thread Size:

3500.0 pounds per square inch

NSN 4720-01-067-9163

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches working
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 2nd end
Specification Data:
Mil-h-13531b, type ii, class a professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0
Mil-std (military Standard):
Mil-h-13531 spec.