

View Online at <https://aerobasegroup.com/nsn/4720-01-068-1375>

Cross Sectional Shape:

Round

Inside Diameter:

2.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Bolt Circle Diameter:

5.000 inches 1st end

Flange Thickness:

0.500 inches 2nd end

Outside Diameter:

2.875 inches

Minimum Inside Bending Radius:

24.000 inches

Exterior Color:

Black

Bolt Hole Quantity:

6 2nd end

Flange Outside Diameter:

6.125 inches 2nd end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.562 inches 2nd end

Raised Face Height:

0.010 inches and 0.020 inches 2nd end

Raised Face Diameter:

3.281 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 2nd end

Features Provided:

Reusable end fittings

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

350.0 pounds per square inch

Hydrostatic Test Pressure:

700.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

37.812 inches working

Flange Style:

Round w/ bolt holes 2nd end

Special Features:

90.0 degrees hose elbow located 17.500 in.From first end

Media For Which Designed:

Fuel/oil, hydrocarbon and water, fresh and water, salt single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0