NSN 4720-01-068-1722

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-068-1722 **Cross Sectional Shape:** Round **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 6.000 inches **Quick Disconnect Size:** 1.000 inches 2nd end **Connection Style:** Push (internal) 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Internal quick disconnect 1st end **Burst Test Pressure:** 750.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 150.0 pounds per square inch **Hydrostatic Test Pressure:** 250.0 pounds per square inch **Outer Covering Environmental Protection:** Alcohol resistant and oil resistant and water resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 66.000 inches **Special Features:** Female end has 2 washers, 1 lanyard p/n 9m59-3-080p, 2 sleeve p/n 9m306-7, 1 streamer p/n st9m405-7 Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4720-01-068-1722

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0