Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-068-6435

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 180.0 degrees fahrenheit single response
Outside Diameter:
0.512 inches
Minimum Inside Bending Radius:
1.500 inches
Exterior Color:
Orange
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
40000.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and outer layer molded polyurethane
Maximum Operating Pressure:
10000.0 pounds per square inch
Thread Size:
1.188 inches 2nd end
Hydrostatic Test Pressure:
20000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
120.000 inches
Special Features:
Each end equiped w/a check valve
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0