Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-069-6422

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.438 inches
Outside Diameter:
0.734 inches
Minimum Inside Bending Radius:
5.750 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer spirally laid corrosion resistant steel wire and 2nd layer spirally laid corrosion resistant steel wire and outer layer braided steel wire
Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 3000.0 pounds per square inch
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size:
Maximum Operating Pressure:   3000.0 pounds per square inch   Thread Size:   0.750 inches 1st end
Maximum Operating Pressure:   3000.0 pounds per square inch   Thread Size:   0.750 inches 1st end   Seat Angle:
Maximum Operating Pressure:   3000.0 pounds per square inch   Thread Size:   0.750 inches 1st end   Seat Angle:   12.0 degrees 1st end
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:Smooth
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:
Maximum Operating Pressure:3000.0 pounds per square inch3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st end12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:Unjf 1st end
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:
Maximum Operating Pressure:3000.0 pounds per square inch3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:Unif 1st endShelf Life:N/a
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:Unif 1st endShelf Life:
Maximum Operating Pressure:   3000.0 pounds per square inch   Thread Size:   0.750 inches 1st end   Seat Angle:   12.0 degrees 1st end   Haide Surface Condition:   Smooth   Measuring Method And Length:   20.000 inches working   Thread Series Designator:   Unjf 1st end   Shelf Life:   N/a   Unif Of Measure:   Tot of Measure:
Maximum Operating Pressure:3000.0 pounds per square inch3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:Unif 1st endShelf Life:N/a
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endBeat Angle:12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:Unif 1st endShelf Life:NaInt of Measure:
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:12.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:20.000 inches workingThread Series Designator:Unjf 1st endShelf Life:N/aUnit Of Measure:Pemilitarization: