

NSN 4720-01-069-7705 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-069-7705 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.230 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.380 inches **Minimum Inside Bending Radius:** 1.500 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

10.000 millimeters 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.125 inches working

Thread Series Designator:

Iso m 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4720-01-069-7705

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0