## NSN 4720-01-070-7179



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-070-7179 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.173 inches **Tempurature Rating:** -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.343 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 7000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

24.875 inches working

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

## NSN 4720-01-070-7179

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0