Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-070-8242

Cross Section	al Shape:
Round	
Thread Direct	on:
Right-hand 1st	end
Inside Diamet	er:
0.250 inches	
Tempurature I	Rating:
-26.0 degrees	celsius and 121.0 degrees celsius single response
Outside Diam	eter:
0.580 inches	
Minimum Insi	le Bending Radius:
3.375 inches	
Exterior Color	:
Red	
Connection St	yle:
Plain 1st end	
End Connection	on Design:
Straight 1st en	t de la construcción de la const
Connection Ty	ире:
Threaded exter	nal pipe 1st end
Burst Test Pre	essure:
2000.0 pounds	per square inch
Layer Compos	sition And Location:
1st layer braide	d wire and outer layer braided textile yarn
Maximum Ope	erating Pressure:
500.0 pounds p	per square inch
Thread Size:	
0.250 inches 1	st end
Inside Surface	Condition:
Smooth	
Measuring Me	thod And Length:
42.000 inches	excluding end fittings
Special Feature	res:
With hansen m	fg co coupling plug II2-k16 and coupling socket II2-h16 and hoke inc regulator 5514f4b or equiv on one end
Media For Wh	ich Designed:
Refrigerant 12	and refrigerant 13 single response
Thread Series	Designator:
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Measu	re:

## NSN 4720-01-070-8242

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0