## NSN 4720-01-071-2871

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-071-2871

Cross	Sectional	Shape:
-------	-----------	--------

Round

**Inside Diameter:** 

2.000 inches

#### **Tempurature Rating:**

-32.0 degrees celsius single response and 52.0 degrees celsius single response

**Outside Diameter:** 

2.656 inches

**Exterior Color:** 

Black

### **Hose Or Tubing Specification/std Data:**

Mil-h-370 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### First End Fitting Specification/std Data:

Ms27025-11 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Second End Fitting Specification/std Data:

Ms27021-11 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### **Quick Disconnect Size:**

2.000 inches 2nd end

## **Connection Style:**

Cam or lever (external) 2nd end

#### **End Connection Design:**

Straight 2nd end

## **End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

## **Connection Type:**

Internal quick disconnect 1st end

## Features Provided:

Electrostatic discharge capability and reusable end fittings

## Second End Relationship With First End:

Not identical

#### **Burst Test Pressure:**

400.0 pounds per square inch

## First End Swivel Action Capability:

Not included

## **Layer Composition And Location:**

1st layer rubber impregnated braided cotton cord err-100

## **Unable To Decode:**

Unable to decode or unable to decode

#### **Maximum Operating Pressure:**

125.0 pounds per square inch

#### **Unable To Decode:**

Unable to decode or unable to decode

# NSN 4720-01-071-2871

Nonmetallic Hose Assembly - Page 2 of 2



# **Outer Covering Environmental Protection:** Fuel resistant and oil resistant and mildew resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 10.300 inches excluding end fittings **Second End Swivel Action Capability:** Not included **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Specification Or Standard:** 2 type Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A542a0

Mil-std (military Standard):

Mil-h-370 spec.