

View Online at <https://aerobasegroup.com/nsn/4720-01-074-4989>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 1000.0 degrees fahrenheit single response

Flange Thickness:

0.297 inches 1st end

Outside Diameter:

2.254 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Center To Center Distance Between Bolt Holes Along Width:

1.812 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.812 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.375 inches 2nd end

Flange Width:

2.375 inches 2nd end

Connection Style:

Plain swivel 1st end

Bolt Hole Diameter:

0.266 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

200.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

50.0 pounds per square inch

Hydrostatic Test Pressure:

100.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

12.234 inches working

Flange Style:

Rectangular (includes square) 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0