Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-076-0445

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response	
Outside Diameter:	
0.720 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel, plain 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 2nd end	
Features Provided:	
Perforated outer cover	
Burst Test Pressure:	
4500.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided fabric and 2nd layer braided fabric and outer layer mold	led rubber, synthetic
Maximum Operating Pressure:	
1125.0 pounds per square inch	
Thread Size:	
0.375 inches 1st end	
Hydrostatic Test Pressure:	
2250.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
19.812 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Npt 1st end	

## NSN 4720-01-076-0445

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

