Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-077-2920

_	
	cross Sectional Shape:
	lound
-	hread Class:
-	b 1st end
т	hread Direction:
	light-hand 1st end
	nside Diameter:
-	.188 inches
	empurature Rating:
-6	65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
0	outside Diameter:
0	.343 inches
N	linimum Inside Bending Radius:
	.000 inches
С	connection Style:
S	wivel nut flare 2nd end
E	nd Connection Design:
S	traight 1st end
С	connection Type:
Т	hreaded internal tube 1st end
F	eatures Provided:
E	lectrostatic discharge capability
В	Burst Test Pressure:
1	2000.0 pounds per square inch
L	ayer Composition And Location:
С	Outer layer braided corrosion resistant steel wire
N	laximum Operating Pressure:
1	500.0 pounds per square inch
т	hread Size:
0	.438 inches 1st end
S	eat Angle:
3	7.0 degrees 2nd end
Η	lydrostatic Test Pressure:
3	000.0 pounds per square inch
F	low Angle:
4	5.0 degrees 2nd end
lr	nside Surface Condition:
S	mooth
N	leasuring Method And Length:
1	8.000 inches working
т	hread Series Designator:
U	Inf 2nd end

Nonmetallic Hose Assembly - Page 2 of 2

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

