Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-077-9147

view Online at https://aerobasegroup.com/nsn/4720-01-077-9147	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.298 inches	
Tempurature Rating:	
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response	
Dutside Diameter:	
.510 inches	
Minimum Inside Bending Radius:	
2.500 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Fhreaded internal tube 1st end	
Burst Test Pressure:	
4000.0 pounds per square inch	
ayer Composition And Location:	
st layer spirally wrapped corrosion resistant steel fabric and 2nd layer spirally wrapped corrosion resista	nt steel fabric and outer layer
raided corrosion resistant steel wire	
Naximum Operating Pressure:	
3000.0 pounds per square inch	
hread Size:	
0.563 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
45.000 inches working	
Special Test Features:	
Navord od42046	
Thread Series Designator:	
Unjf 1st end	

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0