## NSN 4720-01-078-4698

**Cross Sectional Shape:** 

Round

Thread Class: 2a 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-078-4698

Tempurature Rating:				
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response				
Outside Diameter:				
0.380 inches				
Minimum Inside Bending Radius:				
3.000 inches				
Exterior Color:				
Natural				
Connection Style:				
Swivel nut, inverted flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded external tube 2nd end				
Burst Test Pressure:				
6000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1500.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
45.0 degrees 2nd end				
Hydrostatic Test Pressure:				
3000.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Corrosion resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
10.000 inches working				

## NSN 4720-01-078-4698

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0