NSN 4720-01-078-6782

Unj 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-078-6782

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.620 inches
Outside Diameter:
0.860 inches
Minimum Inside Bending Radius:
3.880 inches
Angle Between Rigid Elbow Fittings In Deg:
90.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
30.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.380 inches working
Thread Series Designator:

NSN 4720-01-078-6782

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0