## NSN 4720-01-078-8113

**Cross Sectional Shape:** 

Corrosion resistant and fuel resistant

**Inside Surface Condition:** 

Smooth

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-078-8113

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.605 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.812 inches
Minimum Inside Bending Radius:
6.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:

## NSN 4720-01-078-8113

Nonmetallic Hose Assembly - Page 2 of 2



28.250 inches working

**Thread Series Designator:** 

Unj 2nd end

Shelf Life:

----

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0