## NSN 4720-01-078-9939

**Cross Sectional Shape:** 

Cold resistant and water resistant

**Inside Surface Condition:** 

Smooth

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-078-9939

2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
Outside Diameter:
0.415 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Blue
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated rayon fabric
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:

## NSN 4720-01-078-9939

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
36.000 inches working
Special Features:
Replaceable valve depressor furnished in elbow end
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0