NSN 4720-01-079-0892

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-079-0892

| Thread Class: |
|---|
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 1.125 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.500 inches |
| Minimum Inside Bending Radius: |
| 9.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting cadmium 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 2500.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| 1st layer braided textile yarn err-100 |
| Maximum Operating Pressure: |
| 625.0 pounds per square inch |
| Thread Size: |
| 1.625 inches 1st end |

NSN 4720-01-079-0892

Nonmetallic Hose Assembly - Page 2 of 2



| Seat Angle: |
|---|
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 1250.0 pounds per square inch |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 108.000 inches |
| Special Features: |
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |