Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-079-0892

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
9.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
2500.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided textile yarn err-100
Maximum Operating Pressure:
625.0 pounds per square inch
Thread Size:
1.625 inches 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 1250.0 pounds per square inch Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 108.000 inches **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0