
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-079-4029

ross Sectional Shape:
ound
nread Class:
o 1st end
nread Direction:
ight-hand 1st end
side Diameter:
312 inches
empurature Rating:
5.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
utside Diameter:
575 inches
inimum Inside Bending Radius:
000 inches
onnection Style:
wivel nut flare 1st end
nd Connection Design:
traight 1st end
onnection Type:
nreaded internal tube 1st end
urst Test Pressure:
0500.0 pounds per square inch
ayer Composition And Location:
st layer spirally wrapped corrosion resistant steel fabric and 2nd layer spirally wrapped corrosion resistant steel fabric and outer lay
aided corrosion resistant steel wire
aximum Operating Pressure:
000.0 pounds per square inch
nread Size:
562 inches 1st end
eat Angle:
7.0 degrees 1st end
ydrostatic Test Pressure:
000.0 pounds per square inch
side Surface Condition:
mooth
easuring Method And Length:
0.750 inches working
nread Series Designator:
njf 1st end
helf Life:
/a
nit Of Measure:

NSN 4720-01-079-4029

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

