## NSN 4720-01-080-3898

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-080-3898

Cross Sectional Shape:						
Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.188 inches						
Tempurature Rating:						
-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response						
Outside Diameter:						
Between 0.304 inches and 0.333 inches						
Minimum Inside Bending Radius:						
2.000 inches						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Burst Test Pressure:						
7000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
1500.0 pounds per square inch						
Thread Size:						
0.438 inches 1st end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
3000.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
11.500 inches working						
Thread Series Designator:						
Unjf 1st end						
Shelf Life:						

## NSN 4720-01-080-3898

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0