NSN 4720-01-080-4808

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-080-4808

Cross Sectional Snape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.594 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Internal support
Burst Test Pressure:
750.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.000 inches working
Special Features:
Includes one nameplate, strap andlabel
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-080-4808

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0