Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-082-2837

Cross Sec	tional Shape:
Round	
Thread Cl	ass:
3b 1st end	
Thread Di	rection:
Right-hanc	1st end
Inside Dia	meter:
0.875 inch	es
Tempurat	ure Rating:
-40.0 degre	ees fahrenheit and 300.0 degrees fahrenheit single response
Outside D	iameter:
1.203 inch	es
Minimum	Inside Bending Radius:
7.375 inch	es
Connectio	n Style:
Swivel nut	flare 1st end
End Conn	ection Design:
Straight 2n	d end
Connectio	n Type:
Threaded i	nternal tube 1st end
Thready C	ty Per Inch (tpi):
14 1st end	
Burst Tes	Pressure:
1500.0 pou	inds per square inch
Layer Con	nposition And Location:
1st layer b	raided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric
Maximum	Operating Pressure:
375.0 pour	nds per square inch
Thread Siz	ze:
0.750 inch	es 2nd end
Seat Angle	2:
37.0 degre	es 1st end
Hydrostat	c Test Pressure:
750.0 pour	nds per square inch
Outer Cov	ering Environmental Protection:
Oil resistar	and ozone resistant
Inside Sur	face Condition:
Smooth	
Measuring	Method And Length:
12.250 inc	nes
Media For	Which Designed:
	/drocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0