NSN 4720-01-083-8091

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-083-8091

Cross Sectional Shape:
Round
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Quick Disconnect Size:
0.438 inches 2nd end
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
2750.0 pounds per square inch
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches excluding end fittings
Special Features:
Furnished w/valve adapter w/chain, coupler and quick disconnect nipple
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4720-01-083-8091

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0