Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-085-3991

Crees Sectional Shares
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
12.00 millimeters 2nd end
Seat Angle:
37.0 degrees 2nd end
Vacuum In Torr:
28.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.500 inches working
Thread Series Designator:
Iso m 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4720-01-085-3991

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

